Intellectual Journal of Energy Harvesting and Storage
Vol. 4, No. 2, December 2026, pp. 90~96
ISSN: 2963-6272, DOI: 10.11591/ehs.v4i2.pp90-96

Self-healing smart grid: how automation reduces blackouts and power failures

Kalagotla Chenchireddy, Bosu Saikiran, Borra Fhanindra, Medaboina Ranjith, Saka Rahul, Vallapu Saicharan
Department of Electrical and Electronics Engineering, Geethanjali College of Engineering and Technology, Hyderabad, India

Article Info

Article history:

Received Feb 14, 2026
Revised Mar 6, 2026
Accepted Oct 31, 2026

Keywords:

Blackout prevention
Fault detection, isolation, and restoration
Power system reliability
Self-healing smart grid
Smart grid automation

ABSTRACT

Modern societies depend heavily on a continuous and reliable supply of electricity, yet traditional power grids are increasingly vulnerable to outages caused by equipment failures, extreme weather, cyber threats, and rising demand. Blackouts and power failures not only disrupt daily life but also lead to significant economic losses and safety risks. In response to these challenges, self-healing smart grids have emerged as a transformative solution. By integrating advanced automation, sensors, real-time data analytics, and intelligent control systems, self-healing smart grids can detect, isolate, and respond to faults automatically—often within seconds. This capability greatly reduces the frequency, duration, and impact of power outages. As automation becomes more sophisticated, self-healing smart grids are redefining how electrical networks operate, shifting from reactive systems to proactive and resilient infrastructures that ensure greater reliability and efficiency in power delivery.

This is an open access article under the CC BY-SA license.

Corresponding Author:

Kalagotla Chenchireddy
Department of Electrical Engineering, Geethanjali College of Engineering and Technology
Hyderabad, Telangana, India
Email: Chenchireddy.kalagotla@gmail.com

1. INTRODUCTION

Electric power systems form the backbone of modern civilization, supporting industries, healthcare, communication, transportation, and domestic life. A reliable electricity supply is essential for economic stability and social well-being. However, traditional power grids are increasingly challenged by aging infrastructure, rising electricity demand, integration of renewable energy sources, and extreme weather events. These challenges often lead to frequent blackouts and power failures, causing inconvenience to consumers and severe economic losses [1].

Traditional power grids operate on a centralized and largely manual control structure. Fault detection and restoration processes require human intervention, which increases outage duration and operational risks. As the complexity of power systems grows, these conventional approaches are no longer sufficient. Self-healing smart grids represent a revolutionary advancement in power system engineering. By incorporating automation, digital communication, intelligent sensors, and real-time analytics, self-healing grids can automatically detect faults, isolate affected areas, and restore power with minimal or no human intervention. This case study explores how automation in self-healing smart grids reduces blackouts and power failures, with a focus on real-world implementation and outcomes [2].

2. THE COMPREHENSIVE THEORETICAL BASIS

A self-healing smart grid is an advanced electrical power system that uses automation, real-time monitoring, and intelligent control technologies to automatically detect, isolate, and recover from faults in the network. Unlike traditional power grids that rely heavily on manual intervention, a self-healing smart grid continuously monitors system conditions using smart sensors, communication networks, and intelligent electronic devices (IEDs). When a disturbance such as a line fault or equipment failure occurs, the system quickly identifies the problem, isolates the affected section, and reroutes power through alternate paths to restore electricity with minimal disruption. By integrating technologies such as supervisory control and data acquisition (SCADA), advanced distribution management systems (ADMS), and artificial intelligence, self-healing smart grids significantly reduce blackout duration, improve power reliability, enhance grid resilience, and support the integration of renewable energy sources [3].

Blackouts happen due to a combination of technical, environmental, and operational factors that disrupt the normal flow of electricity in a power system. Common causes include equipment failures such as damaged transformers or transmission lines, overloads caused by sudden increases in electricity demand, and aging infrastructure that cannot handle modern power requirements. Natural events like storms, lightning, floods, earthquakes, and falling trees can also damage power lines and substations, leading to widespread outages. In addition, human errors, inadequate system maintenance, cyberattacks, and poor coordination between generation and distribution systems can contribute to blackouts. When these disturbances are not detected and managed quickly, they can cascade through the grid, causing large-scale power failures [4].

Automation helps by enabling the power grid to respond to faults quickly and intelligently without relying on manual intervention. Through real-time monitoring, automated control systems can instantly detect abnormalities such as overloads or line faults, isolate the affected section of the grid, and restore power by rerouting electricity through alternative paths. This rapid response prevents small disturbances from spreading into large-scale blackouts and significantly reduces outage duration. By using technologies such as sensors, IEDs, SCADA, and ADMS, automation improves the reliability, efficiency, and resilience of the power grid while ensuring continuous and stable electricity supply [5].

The key parts of a self-healing smart grid include smart sensors and meters that continuously monitor the condition of the power system and detect faults in real time. IEDs and automated switches help isolate faulty sections quickly to prevent the spread of outages. Communication networks enable fast, two-way data exchange between grid components and control centers. Control systems such as SCADA and ADMS analyze data and make automated decisions for fault recovery. Together, these components allow the grid to automatically restore power, reduce blackouts, and improve overall reliability in a simple and efficient manner.

When a fault occurs, a smart grid fixes it through a series of automated steps. First, smart sensors and meters continuously monitor the system and immediately detect any abnormal condition, such as a short circuit or line failure. Next, the control system analyzes the data to identify the exact location of the fault. Then, automated switches and circuit breakers isolate the faulty section to prevent the problem from spreading to the rest of the grid. After isolation, the system automatically reroutes electricity through alternative paths to restore power to unaffected areas. Finally, the grid confirms stable operation and alerts maintenance teams to repair the damaged equipment, ensuring fast recovery and minimal power interruption.

Distributed energy resources such as solar panels and battery storage systems play an important role in improving the performance of a self-healing smart grid. Solar energy provides local power generation, reducing dependence on centralized power plants and long transmission lines that are more vulnerable to faults. Batteries store excess energy and supply power during outages or peak demand periods, helping maintain grid stability. When a fault occurs, these distributed resources can continue supplying electricity to nearby areas or operate in islanded mode, allowing faster recovery and reduced blackout impact. By supporting automation and self-healing functions, solar and battery systems enhance grid resilience, reliability, and sustainability [6]–[10].

The main benefits of self-healing smart grids include improved power reliability and reduced blackout duration by automatically detecting and fixing faults in the system. They minimize human intervention, allowing faster response to failures and preventing small disturbances from turning into large outages. Self-healing smart grids also enhance grid resilience against natural disasters and equipment failures, improve operational efficiency, and reduce maintenance costs through real-time monitoring and predictive analysis. In addition, they support the integration of renewable energy sources such as solar and wind, improve energy efficiency, and ensure a more stable, secure, and sustainable electricity supply.

3. METHOD

The method describes the step-by-step approach used to achieve self-healing in a smart grid system. It focuses on how automation detects faults, isolates faulty sections, and restores power automatically (see in Figure 1).




Figure 1. Method flowchart

3.1. Step 1: data collection and monitoring

Data collection and monitoring is a crucial part of a self-healing smart grid, as it allows the system to continuously observe the health and performance of the electrical network. Smart sensors, meters, and IEDs collect real-time data on voltage, current, frequency, and load conditions across the grid. This information is transmitted through communication networks to control centers, where advanced systems like SCADA and distribution management software analyze it to detect anomalies or potential faults. Continuous monitoring enables the grid to respond immediately to disturbances, predict equipment failures, optimize energy flow, and support automated fault isolation and restoration, making the system more reliable and efficient [11].

3.2. Step 2: fault detection

Fault detection is the process by which a self-healing smart grid identifies problems or disturbances in the power system as soon as they occur. Using smart sensors, meters, and IEDs, the grid continuously

monitors voltage, current, and other electrical parameters to detect abnormalities such as short circuits, line breaks, or equipment failures. Advanced control systems analyze this data in real time to pinpoint the exact location and type of fault. Early and accurate fault detection is essential because it allows the grid to isolate the affected section quickly, prevent the problem from spreading, and initiate automatic restoration, reducing blackout duration and improving overall power reliability [12].

3.3. Step 3: fault location identification

Fault location identification is the process in a self-healing smart grid that determines the exact place where a fault has occurred. After fault detection, advanced sensors, IEDs, and communication networks send data about current, voltage, and line conditions to control systems like SCADA or ADMS. These systems analyze the information using algorithms to pinpoint the specific line, section, or equipment that caused the disturbance. Accurate fault location is critical because it allows the grid to isolate only the affected area, restore power to the rest of the network quickly, and guide maintenance teams directly to the problem, minimizing downtime and improving overall grid reliability [13].

3.4. Step 4: fault isolation

Fault isolation is the process in a self-healing smart grid where the section of the network affected by a fault is separated from the rest of the system to prevent the problem from spreading. Once a fault is detected and its location is identified, automated switches and circuit breakers quickly open to isolate the damaged line, transformer, or equipment. This ensures that only the faulty part of the grid is disconnected while electricity continues to flow to unaffected areas. Fault isolation is a key step in reducing the impact of power failures, minimizing blackout areas, and enabling the grid to restore service quickly and efficiently [14].

3.5. Step 5: service restoration

Service restoration is the process in a self-healing smart grid where electricity supply is quickly restored to areas affected by a fault. After the faulty section is detected, located, and isolated, the grid automatically reroutes power through alternative lines or switches to supply electricity to as many customers as possible. Control systems like SCADA or ADMS coordinate this restoration in real time, ensuring minimal disruption. Service restoration reduces blackout duration, improves reliability, and allows the grid to maintain continuous operation while maintenance teams repair the damaged equipment [14].

3.6. Step 6: system verification and learning

System verification and learning is the final step in a self-healing smart grid's fault management process, ensuring that the grid is stable and improving its performance over time. After a fault has been detected, isolated, and service restored, the control systems verify that all sections of the network are operating normally, checking voltage, current, and load conditions. Simultaneously, the grid records data from the event, which can be analyzed using machine learning and advanced analytics to identify patterns, improve fault prediction, and optimize future automated responses. This continuous learning helps the grid become smarter, more resilient, and better at preventing and responding to future outages [15].

4. RESULTS AND DISCUSSION

The implementation of a self-healing smart grid using automated sensing, communication, and control techniques produced significant improvements in grid performance and reliability [16]–[19].

4.1. Reduction in power outage duration

Reduction in power outage duration is one of the key advantages of a self-healing smart grid. By automatically detecting faults, identifying their location, isolating the affected sections, and rerouting power through alternative paths, the grid can restore electricity much faster than traditional systems. Real-time monitoring and automated control systems ensure that service is resumed within minutes in many cases, instead of hours. This not only minimizes inconvenience to consumers but also reduces economic losses, protects critical infrastructure, and improves overall reliability and resilience of the power supply.

4.2. Improved fault detection and isolation

Improved fault detection and isolation is a major benefit of a self-healing smart grid, allowing the system to quickly identify and respond to problems before they escalate into widespread outages. Advanced sensors, IEDs, and real-time monitoring enable the grid to detect faults instantly and determine their exact location. Automated switches and circuit breakers then isolate only the affected section, preventing the fault from spreading to the rest of the network. This precise and rapid action reduces the area impacted by outages,

ensures faster restoration of service, and significantly enhances the reliability and stability of the power system.

4.3. Faster service restoration

Faster service restoration is a key advantage of self-healing smart grids, enabling electricity to be returned to affected areas quickly after a fault occurs. Once a problem is detected, located, and isolated, the system automatically reroutes power through alternative paths to maintain supply to as many customers as possible. Advanced control systems like SCADA and ADMS coordinate these actions in real time, minimizing downtime. This rapid restoration not only reduces the inconvenience to consumers but also limits economic losses, supports critical services, and enhances the overall reliability and resilience of the grid.

4.4. Enhanced system reliability

Enhanced system reliability is a core benefit of self-healing smart grids, ensuring that electricity is delivered consistently and with minimal interruptions. By combining real-time monitoring, automated fault detection, isolation, and service restoration, the grid can prevent small disturbances from escalating into large-scale blackouts. Continuous data collection and system learning allow the grid to anticipate potential problems and respond proactively. As a result, power delivery becomes more stable, maintenance becomes more efficient, and both consumers and critical infrastructure experience fewer disruptions, making the overall power system much more dependable.

4.5. Impact of automation

Impact of automation in a self-healing smart grid is profound, as it transforms how the power system responds to faults and manages energy flow. Automation enables real-time monitoring, instant fault detection, precise isolation of affected sections, and rapid service restoration without human intervention. This reduces outage duration, limits the area affected by blackouts, and improves overall system reliability. Additionally, automation allows predictive maintenance, optimizes load management, supports the integration of renewable energy sources, and enhances operational efficiency. Overall, automation makes the grid smarter, more resilient, and capable of delivering stable, continuous, and reliable electricity to consumers.

4.6. Effectiveness of self-healing method

Effectiveness of self-healing method lies in its ability to minimize the impact of faults and maintain continuous power supply with minimal human intervention. By combining real-time monitoring, automated fault detection, precise isolation, and rapid service restoration, the self-healing approach significantly reduces blackout duration and prevents small disturbances from escalating into widespread outages. The method also enables predictive maintenance, improves system reliability, and enhances grid resilience against natural disasters, equipment failures, and fluctuating demand. Through continuous data collection and learning, the grid becomes increasingly intelligent, making the self-healing method highly effective in ensuring stable, efficient, and dependable electricity delivery.

4.7. Role of communication and sensors

Role of communication and sensors in a self-healing smart grid is critical for enabling real-time monitoring, fault detection, and automated response. Sensors placed throughout the grid continuously measure voltage, current, frequency, and other electrical parameters, detecting abnormalities or disturbances as they occur. Communication networks then transmit this data to control systems such as SCADA or ADMS, allowing rapid analysis and decision-making. Together, sensors and communication infrastructure ensure that faults are quickly identified, isolated, and addressed, enabling faster service restoration, reducing blackout impact, and improving overall reliability and efficiency of the power system. Table 1 presents a comparison between the traditional power grid and the proposed self-healing smart grid in terms of their key operational characteristics.

Table 1. Comparison with traditional power grid

Aspect	Traditional grid	Self-healing smart grid
Fault detection	Manual	Automatic
Response time	Slow	Very fast
Outage area	Large	Limited
Restoration	Manual	Automated
Reliability	Moderate	High

4.8. Practical significance

Practical significance of a self-healing smart grid lies in its ability to make electricity supply more reliable, efficient, and resilient in real-world conditions. By automatically detecting, isolating, and restoring faults, it minimizes blackout duration and reduces disruptions for homes, businesses, and critical infrastructure. The grid's use of sensors, automation, and communication networks lowers operational and maintenance costs while enabling better integration of renewable energy sources like solar and wind. Additionally, it enhances system stability during natural disasters or high-demand periods and supports predictive maintenance, ultimately improving customer satisfaction, reducing economic losses, and ensuring a more sustainable and dependable power supply.

5. CONCLUSION

The self-healing smart grid represents a major advancement in modern power systems. By integrating automation, intelligent sensors, communication networks, and smart control devices, the grid is able to detect faults, isolate faulty sections, and restore power automatically. The study shows that automation significantly reduces the frequency and duration of power outages. Faults are identified quickly, preventing their spread and minimizing large-scale blackouts. Automated switching and intelligent decision-making allow power to be restored faster compared to traditional power grids. In addition, the use of distributed energy resources such as solar power and battery storage improves system resilience. These resources help maintain power supply during disturbances and support local loads when the main grid fails. Overall, the self-healing smart grid improves reliability, efficiency, and power quality. Although challenges such as high initial cost and cybersecurity concerns exist, the benefits of reduced outages, improved customer satisfaction, and enhanced grid stability make self-healing smart grids a promising solution for future power system.

FUNDING INFORMATION

Authors state no funding involved.

AUTHOR CONTRIBUTIONS STATEMENT

This journal uses the Contributor Roles Taxonomy (CRediT) to recognize individual author contributions, reduce authorship disputes, and facilitate collaboration.

Name of Author	C	M	So	Va	Fo	I	R	D	O	E	Vi	Su	P	Fu
Kalagotla Chenchireddy	✓	✓	✓	✓	✓	✓		✓	✓	✓			✓	
Bosu Saikiran	✓		✓	✓			✓			✓	✓		✓	✓
Borra Fhanindra		✓		✓		✓		✓	✓	✓	✓	✓		
Medaboina Ranjith	✓			✓				✓	✓				✓	
Saka Rahul	✓				✓		✓			✓		✓		✓
Vallapu Saicharan		✓							✓					

C : **C**onceptualization
M : **M**ethodology
So : **So**ftware
Va : **Va**lidation
Fo : **Fo**rmal analysis
I : **I**nvestigation
R : **R**esources
D : **D**ata Curation
O : Writing - **O**riginal Draft
E : Writing - Review & **E**diting
Vi : **Vi**sualization
Su : **Su**pervision
P : **P**roject administration
Fu : **Fu**nding acquisition

CONFLICT OF INTEREST STATEMENT

Authors state no conflict of interest.

DATA AVAILABILITY

Data availability is not applicable to this paper as no new data were created or analyzed in this study.

REFERENCES

[1] M. Hatwar *et al.*, "Self-Healing Smart Grid with Time Fault Detection and Predictive Maintenance of Grids," *16th Int. Conf. Adv.*

Comput. Control. Telecommun. Technol. ACT 2025, vol. 1, pp. 1073–1079, 2025.
[2] Jayasudha and K. H. Vishakh, "Review of Self-Healing Mechanisms for an Enhanced Power Grid Resilience," *2025 2nd Int. Conf. Circuits, Power, Intell. Syst. CCPIS 2025*, 2025, 1–6, doi: 10.1109/CCPIS65231.2025.11234269.
[3] M. Goda, M. Abdel-Salam, M. T. EL-Mohandes, and A. Elnozahy, "Electric supply restoration in self-healed smart distribution systems: a review," *Energy Informatics*, vol. 8, no. 1, 2025, doi: 10.1186/s42162-025-00541-5.
[4] E. Reza, M. M. Hasan, J. Alireza, and A. Mohammad, "Effect of Fault Detection on The Resilience and Self-Healing in Islanded Micro-Grids," *Int. J. Smart Electr. Eng.*, vol. 14, no. 3, pp. 133–144, 2025, doi: 10.82234/IJSEE.2025.1210109.
[5] S. Badakhshan, R. A. Jacob, B. Li, P. Wang, and J. Zhang, "Self-healing power systems using reinforcement learning over graphs for controlled grid islanding," *Sustain. Energy, Grids Networks*, vol. 44, 2025, doi: 10.1016/j.segan.2025.101937.
[6] P. K. Sholapurapu, "Power Electronics for IoT-Enabled Smart Grids and Industrial Automation," in *SSRN Electr, Journ.*, Jan. 2025, doi: 10.2139/ssrn.5382142.
[7] S. Wang, Z. Zhao, and Y. Li, "The research progress on power system restoration and resilience analysis: Key technologies and future development trends," *Adv. Resour. Res.*, vol. 5, pp. 2528–2558, 2025.
[8] T. A. Rajaperumal and C. C. Columbus, "Transforming the electrical grid: the role of AI in advancing smart, sustainable, and secure energy systems," *Energy Informatics*, vol. 8, no. 1, pp. 1–15, 2025, doi: 10.1186/s42162-024-00461-w.
[9] M. Sharma and N. Arora, "Advancements in Smart Grid Technology: Revolutionizing Electrical Power Distribution," *J. Curr. Trends Electr. Eng.*, vol. 10, no. 1, pp. 14–26, 2025.
[10] K. Kull, B. Asad, M. A. Khan, M. U. Naseer, A. Kallaste, and T. Vaimann, "Faults, Failures, Reliability, and Predictive Maintenance of Grid-Connected Solar Systems: A Comprehensive Review," *Appl. Sci.*, vol. 15, no. 21, 2025, doi: 10.3390/app152111461.
[11] S. Ness, "Integrating AI Models for Voltage and Current Monitoring in Autonomous Mobile Robots to Prevent Power System Blackouts," *IEEE Access*, vol. 13, pp. 67079–67094, 2025, doi: 10.1109/ACCESS.2025.3560088.
[12] E. Kabalcı, "Power electronics devices and applications for smart grid systems," *Handb. Power Electron. Smart Grids Intell. Energy*, pp. 1–56, 2026, doi: 10.1016/B978-0-323-95045-9.00015-9.
[13] H. Mohammadzade, A. Saffarian, and M. Joorabian, "Cost-effective centralised load shedding method for power system self-healing," *Aust. J. Electr. Electron. Eng.*, pp. 1–12, 2025, doi: 10.1080/1448837X.2025.2544370.
[14] G. Shi, Z. Luo, and R. Wang, "Strategies for Self-Healing and Resilience Enhancement of Distribution Networks under Extreme Events," in *Proc. - 2025 Int. Conf. Adv. Electr. Eng. Comput. Appl. AEECA 2025*, 2025, pp. 326–330, doi: 10.1109/AEECA65693.2025.00064.
[15] S. Y. Lau, L. S. Kenyon, F. V. Hatton, K. Weller, and R. Lloyd, "A self-healing smart grid for Railway Signalling Network," *IEEE Sensors Appl. Symp. SAS*, pp. 1–6, 2025, doi: 10.1109/SAS65169.2025.11105146.
[16] A. Chhabra *et al.*, "Improving predictive reliability and automation of smart grids using the StarNet ensemble model," *Sci. Rep.*, vol. 16, no. 1, 2026, doi: 10.1038/s41598-025-31479-z.
[17] P. Rai and Abhishek, "Next-Generation Smartgrid: Intelligent Energy Networks for a Sustainable Future," *Proc. 2025 12th Int. Conf. Comput. Sustain. Glob. Dev. INDIACom 2025*, 2025, pp. 1–6, doi: 10.23919/INDIACom66777.2025.11115879.
[18] R. Muka, E. Braha, and I. Duro, "Enhancing economic resilience through advanced monitoring and real-time fault detection in smart grids," *Int. Conf. Econ. Business, Innov. Technol.*, 2024, pp pp. 1086-1110.
[19] J. Zhong *et al.*, "Advancing resilience with SDN: A comprehensive review of cyber-physical strategies for smart grid," *Smart Power Energy Secur.*, vol. 1, no. 4, pp. 186–203, 2025, doi: 10.1016/j.spes.2025.12.003.