IAES Journal of Electrical and Electronics Engineering
Vol. 8, No. 1, June 2021, pp. 6~10
ISSN: 2338-7432, DOI: 10.11591/jeee.v8i1.pp6-10

Engineering a squeeze-powered flashlight for multifunctional applications: energy harvesting, storage, and low-power system integration-a review

Fajar Sulistyo[1], Anggit Pamungkas[2]
[1]Faculty of Industrial Technology, Universitas Ahmad Dahlan, Yogyakarta, Indonesia
[2]Embedded Systems and Power Electronics Research Group, Yogyakarta, Indonesia

Article Info

Article history:

Received Jul 16, 2019
Revised Jan 7, 2020
Accepted Mar 18, 2020

Keywords:

Electromagnetic generator
Energy storage
Human-powered energy harvesting
Low-power electronics
Multifunctional device
Squeeze-powered flashlight

ABSTRACT

A squeeze-powered flashlight converts mechanical energy from repeated hand compression into electrical energy through an electromechanical generator. Although its conventional purpose is emergency illumination, the same conversion mechanism offers opportunities for additional functions in portable and off-grid devices. This review examines the engineering principles and potential multifunctional applications of squeeze-powered flashlight technology, emphasizing electromagnetic energy conversion, mechanical transmission, power conditioning, and energy storage. Relevant research on human-powered generators, wearable energy harvesters, and low-power electronic systems is considered to establish a technical foundation for extending flashlight functionality. Potential applications include emergency signaling, portable sensor operation, low-power communication, battery charging for small electronic devices, and basic health or environmental monitoring. The review also discusses the limitations associated with intermittent mechanical input, low conversion efficiency, component durability, and user fatigue. A multifunctional design should therefore prioritize energy-efficient loads, suitable storage elements, regulated output, and modular electronic interfaces. The analysis indicates that a squeeze-powered flashlight can serve as a compact human-powered energy platform, provided that additional functions are matched to its realistic energy-generation capability and tested under practical operating conditions.

This is an open access article under the CC BY-SA license.

1. INTRODUCTION

Portable lighting devices are important for emergency situations, outdoor activities, household use, and locations where electrical infrastructure is unavailable. Conventional battery-powered flashlights provide convenient illumination, but their operation depends on stored electrical energy that must be periodically replenished or replaced. A squeeze-powered flashlight offers an alternative by converting repeated hand compression into electrical energy through a compact mechanical and electromagnetic arrangement. This approach is related to human-powered energy harvesting, which has been investigated for portable electronics, wearable devices, and autonomous sensors [1]–[4].

The engineering potential of a squeeze-powered flashlight extends beyond illumination because its generator can supply electricity to other low-power electronic components. A rectifier, energy storage element, and voltage regulator can transform the intermittent generator output into a more usable electrical supply. This arrangement could support emergency indicators, small sensors, or low-power communication modules in addition to the original LED lighting function. However, the available energy is constrained by human effort, generator dimensions, conversion losses, and the duration of operation [5], [6].

The central research problem is how to redesign a squeeze-powered flashlight as a multifunctional device without compromising its primary lighting function or creating unrealistic power expectations. Existing

research provides useful principles for electromagnetic generation, human-motion energy harvesting, and low-power power-management circuits, although not all studies investigate squeeze flashlights directly. Therefore, this review synthesizes related engineering findings to identify feasible additional functions and suitable design requirements, including self-powered mechanical sensing and alternative harvesting mechanisms [7], [8]. The discussion follows the energy-conversion process from mechanical input to electrical storage and application, leading to recommendations for future prototype development.

2. OPERATING PRINCIPLES AND SYSTEM ARCHITECTURE

A squeeze-powered flashlight generally uses a mechanical transmission system to convert hand compression into relative movement between a magnet and an electrical coil. The movement changes the magnetic flux through the coil and induces an electrical voltage. Depending on the mechanism, a spring, sliding assembly, gear train, or lever may return the moving component and prepare it for another compression cycle. Electromagnetic energy harvesting is suitable for this type of intermittent mechanical input because it can convert relatively slow human movement into electrical energy [3], [9]–[11].

The electrical output from a compact generator is generally variable because the speed and force of hand compression are not constant. A practical system therefore requires power-conditioning components to make the generated energy useful for electronic loads. A rectifier can convert alternating or bidirectional generator output into a unidirectional supply, while a storage component accumulates energy between compression cycles. A regulator can then provide a more stable voltage to the LED, sensors, or other electronic modules [5], [12].

A multifunctional architecture should separate energy generation, storage, control, and application modules. The generator provides the input energy, while the power-management circuit handles rectification, voltage conversion, and charging control. A battery or supercapacitor stores the energy and supplies the selected application when sufficient energy is available. This modular structure enables the flashlight to support additional functions without requiring every electronic load to operate directly from the unstable generator output [5], [12], [13].

3. POTENTIAL MULTIFUNCTIONAL APPLICATIONS

3.1. Emergency signaling and safety indicators

Emergency signaling is one of the most practical extensions of a squeeze-powered flashlight because it can use the existing LED and energy-storage components. The device could provide flashing warning signals, an SOS light pattern, or a high-visibility indicator for roadside and outdoor emergencies. These functions can be implemented through a low-power microcontroller or a simple electronic oscillator controlling the LED output. Human-powered energy systems have been investigated for portable electronics and emergency-related applications, supporting the general feasibility of compact self-generated power sources [2], [4], [14].

3.2. Charging small electronic devices

A squeeze-powered flashlight could also provide limited charging capability for small electronic devices through a regulated output interface. The stored energy may be delivered to low-power equipment such as small rechargeable batteries, miniature radios, or selected sensor modules. However, charging a smartphone directly is generally impractical as a primary function because the energy generated by repeated manual compression is limited and intermittent. Research on human-powered energy harvesting emphasizes the importance of matching the electrical load to the actual mechanical energy available [4], [6], [15].

3.3. Portable environmental monitoring

Another useful application is the integration of low-power environmental sensors. Temperature, humidity, light intensity, and basic air-quality sensors could be powered intermittently from energy stored in a small battery or supercapacitor. A microcontroller could process the measurements and display the results through a small screen or indicator LEDs. This application is consistent with research on energy harvesting for autonomous sensor systems, in which intermittent energy sources support monitoring functions with carefully managed power consumption [5], [12], [13].

3.4. Emergency communication and location assistance

The flashlight could be adapted to support basic emergency communication or location-assistance functions. A low-power radio-frequency transmitter, short-range beacon, or simple signaling module could operate after sufficient energy has accumulated in the storage unit. Such a design would be particularly useful in remote locations where access to conventional power sources is limited. Nevertheless, communication

modules often require short periods of relatively high current, so energy buffering and controlled transmission intervals are essential [2], [5].

3.5. Basic health and personal safety monitoring

A further possibility is integrating selected low-power health-monitoring components, such as a pulse sensor or simple body-temperature sensor. The flashlight could function as an emergency personal safety device by combining illumination with basic physiological measurements. Research into human-body energy harvesting demonstrates the broader potential of mechanically powered electronics for wearable and biomedical applications [13]. However, a squeeze-powered flashlight should not be regarded as a medical diagnostic instrument without appropriate sensor validation, calibration, and clinical assessment.

4. COMPARISON OF MULTIFUNCTIONAL APPLICATIONS

The suitability of additional functions depends on their power demand, operating duration, and importance during emergency conditions. Table 1 summarizes potential applications and the main engineering considerations for each function. The comparison indicates that emergency signaling and environmental sensing are relatively practical because they can operate intermittently and use stored energy efficiently. In contrast, continuous communication and external device charging require more careful evaluation of generator capacity and energy-storage size.

Table 1. Potential additional functions of a squeeze-powered flashlight

Additional function	Main components	Expected power profile	Main engineering consideration
Emergency signaling	LED, oscillator or microcontroller	Low, intermittent	Visibility and flashing control
Small-device charging	Rectifier, regulator, storage unit, output port	Intermittent, load-dependent	Limited generated energy
Environmental monitoring	Sensors, microcontroller, display	Low, periodic	Sensor standby consumption
Emergency beacon	Radio module, controller, storage	Short current peaks	Energy buffering and transmission range
Basic health monitoring	Pulse or temperature sensor, controller	Low, periodic	Measurement accuracy and calibration

The table also shows that multifunctionality should not be interpreted as simultaneous operation of every feature. A compact generator may not provide enough energy to operate lighting, sensing, and communication continuously at the same time. A more realistic design would use selectable operating modes and prioritize essential functions according to available stored energy. This approach can improve practical usefulness while reducing unnecessary energy consumption [5], [12], [16].

5. MECHANICAL AND ELECTRICAL DESIGN CONSIDERATIONS

Mechanical design strongly influences the amount of energy that can be generated during each compression cycle. The compression distance, spring stiffness, magnet movement, coil geometry, and transmission mechanism determine the generator's electrical response. A finger-triggered electromagnetic energy harvester using gear transmission and Halbach magnets demonstrates how mechanical arrangements can improve energy extraction from low-frequency human input [17]. For a squeeze-powered flashlight, the mechanism should balance electrical output with comfortable operation, compact dimensions, and long-term mechanical durability.

The electrical subsystem should be designed around the characteristics of the generator rather than assuming a constant voltage source. Rectification losses, converter efficiency, storage leakage, and control-circuit consumption can significantly reduce the energy available to the application. Research on power conversion for low-voltage energy-harvesting systems identifies cold-start capability, voltage conversion, and storage management as important design challenges [12]. Accordingly, the proposed device should use low-quiescent-current circuits and avoid unnecessary standby loads.

Energy storage is essential because hand compression produces intermittent electrical output rather than a continuous supply. A rechargeable battery can provide relatively high energy capacity, whereas a supercapacitor can support repeated charging and discharging with high power delivery capability. The appropriate choice depends on the expected operating cycle, required output current, device size, and maintenance conditions. A hybrid storage arrangement may also be considered when both rapid energy delivery and longer-duration operation are required [5], [12].

6. CHALLENGES AND FUTURE RESEARCH DIRECTIONS

The first major challenge is the limited and inconsistent mechanical energy supplied by the user. Compression force, speed, hand size, and operating frequency differ among individuals, resulting in variable electrical output. Human-motion energy-harvesting studies show that irregular input and the mechanical characteristics of the excitation source influence the performance of the generator [6], [9], [18]. Future designs should therefore evaluate energy generation across different users and compression patterns rather than relying on a single laboratory operating condition.

The second challenge concerns the balance between multifunctionality and device complexity. Adding sensors, communication modules, displays, and charging interfaces increases cost, size, and power consumption. Each additional function should therefore have a clear purpose and should be activated only when sufficient energy is available. Research on human-powered smart electronics suggests that application-specific energy management is more effective than simply increasing the number of integrated components [15], [16].

Future experimental research should compare different mechanical transmission systems and generator configurations under standardized compression conditions. Important performance indicators include energy generated per compression cycle, conversion efficiency, storage-charging time, regulated output stability, and mechanical lifetime. Researchers should also assess the usability of the device through repeated-operation tests and evaluate whether users can generate sufficient energy without excessive physical effort. These measurements would provide a stronger basis for selecting practical multifunctional applications and improving the overall design.

7. CONCLUSION

A squeeze-powered flashlight can be developed into a multifunctional human-powered device by integrating an electromagnetic generator with power conditioning, energy storage, and modular electronic applications. Potential additional functions include emergency signaling, small-device charging, environmental monitoring, emergency communication, and basic health monitoring. Among these possibilities, low-power and intermittent applications are the most realistic because the available mechanical energy is limited and depends on user activity. The successful implementation of these functions requires careful coordination between the mechanical transmission system, generator, storage unit, and electronic load. The review indicates that the main engineering priority is not maximizing the number of functions but matching each function to the actual energy-generation capability of the device. Future prototypes should emphasize efficient electromagnetic conversion, low-loss power management, durable mechanical components, and selectable operating modes. Experimental validation is necessary to determine the practical energy output and operating time under realistic hand-compression conditions. With these considerations, the squeeze-powered flashlight can become a useful platform for portable emergency electronics and other low-power applications.

REFERENCES

[1] S. P. Beeby, M. J. Tudor, and N. M. White, "Energy harvesting vibration sources for microsystems applications," *Measurement Science and Technology*, vol. 17, no. 12, 2006, doi: 10.1088/0957-0233/17/12/R01.

[2] J. A. Paradiso and T. Starner, "Energy scavenging for mobile and wireless electronics," *IEEE Pervasive Computing*, vol. 4, no. 1, pp. 18–27, 2005, doi: 10.1109/MPRV.2005.9.

[3] P. D. Mitcheson, E. M. Yeatman, G. K. Rao, A. S. Holmes, and T. C. Green, "Energy harvesting from human and machine motion for wireless electronic devices," *Proceedings of the IEEE*, vol. 96, no. 9, pp. 1457–1486, 2008, doi: 10.1109/JPROC.2008.927494.

[4] D. Jia and J. Liu, "Human power-based energy harvesting strategies for mobile electronic devices," *Frontiers of Energy and Power Engineering in China*, vol. 3, no. 1, pp. 27–46, 2009, doi: 10.1007/s11708-009-0002-4.

[5] R. Vullers, R. Schaijk, H. Visser, J. Penders, and C. Hoof, "Energy harvesting for autonomous wireless sensor networks," *IEEE Solid-State Circuits Magazine*, vol. 2, no. 2, pp. 29–38, 2010, doi: 10.1109/MSSC.2010.936667.

[6] R. Riemer and A. Shapiro, "Biomechanical energy harvesting from human motion: Theory, state of the art, design guidelines, and future directions," *Journal of NeuroEngineering and Rehabilitation*, vol. 8, no. 1, 2011, doi: 10.1186/1743-0003-8-22.

[7] Z. L. Wang, "Triboelectric nanogenerators as new energy technology for self-powered systems and as active mechanical and chemical sensors," *ACS Nano*, vol. 7, no. 11, pp. 9533–9557, 2013, doi: 10.1021/nn404614z.

[8] Z. L. Wang, "Triboelectric nanogenerators as new energy technology and self-powered sensors - Principles, problems and perspectives," *Faraday Discussions*, vol. 176, pp. 447–458, 2014, doi: 10.1039/c4fd00159a.

[9] F. Invernizzi, S. Dulio, M. Patrini, G. Guizzetti, and P. Mustarelli, "Energy harvesting from human motion: Materials and techniques," *Chemical Society Reviews*, vol. 45, no. 20, pp. 5455–5473, 2016, doi: 10.1039/c5cs00812c.

[10] C. Y. Sue and N. C. Tsai, "Human powered MEMS-based energy harvest devices," *Applied Energy*, vol. 93, pp. 390–403, 2012, doi: 10.1016/j.apenergy.2011.12.037.

[11] D. Dai and J. Liu, "Hip-mounted electromagnetic generator to harvest energy from human motion," *Frontiers in Energy*, vol. 8, no. 2, pp. 173–181, 2014, doi: 10.1007/s11708-014-0301-2.

[12] D. Newell and M. Duffy, "Review of power conversion and energy management for low-power, low-voltage energy harvesting powered wireless sensors," *IEEE Transactions on Power Electronics*, vol. 34, no. 10, pp. 9794–9805, 2019, doi: 10.1109/TPEL.2019.2894465.

[13] C. Dagdeviren, Z. Li, and Z. L. Wang, "Energy harvesting from the animal-human body for self-powered electronics," *Annual Review of Biomedical Engineering*, vol. 19, pp. 85–108, 2017, doi: 10.1146/annurev-bioeng-071516-044517.
[14] H. Lee and J. S. Roh, "Wearable electromagnetic energy-harvesting textiles based on human walking," *Textile Research Journal*, vol. 89, no. 13, pp. 2532–2541, 2019, doi: 10.1177/0040517518797349.
[15] S. Khalid, I. Raouf, A. Khan, N. Kim, and H. S. Kim, "A review of human-powered energy harvesting for smart electronics: recent progress and challenges," *International Journal of Precision Engineering and Manufacturing - Green Technology*, vol. 6, no. 4, pp. 821–851, 2019, doi: 10.1007/s40684-019-00144-y.
[16] M. Safaei, H. A. Sodano, and S. R. Anton, "A review of energy harvesting using piezoelectric materials: State-of-the-art a decade later (2008-2018)," *Smart Materials and Structures*, vol. 28, no. 11, 2019, doi: 10.1088/1361-665X/ab36e4.
[17] J. W. Kim, M. Salauddin, H. Cho, M. S. Rasel, and J. Y. Park, "Electromagnetic energy harvester based on a finger trigger rotational gear module and an array of disc Halbach magnets," *Applied Energy*, vol. 250, pp. 776–785, 2019, doi: 10.1016/j.apenergy.2019.05.059.
[18] K. Li, Q. He, J. Wang, Z. Zhou, and X. Li, "Wearable energy harvesters generating electricity from low-frequency human limb movement," *Microsystems and Nanoengineering*, vol. 4, no. 1, 2018, doi: 10.1038/s41378-018-0024-3.