IAES Journal of Electrical and Electronics Engineering
Vol. 9, No. 1, June 2022, pp. 1~5
ISSN: 2338-7432, DOI: 10.11591/jeee.v9i1.pp1-5

Smart electrical plugs for energy conservation: a review of standby power reduction, consumption profiling, and demand-side management

Tole Sutikno[1], Anggit Pamungkas[2], Watra Arsadiando[2]
[1]Faculty of Industrial Technology, Universitas Ahmad Dahlan, Yogyakarta, Indonesia
[2]Embedded Systems and Power Electronics Research Group, Yogyakarta, Indonesia

Article Info

Article history:

Received Jan 6, 2020
Revised Aug 6, 2020
Accepted Nov 28, 2020

Keywords:

Consumption profiling
Demand-side management
Energy conservation
Energy monitoring
Home energy management
Smart electrical plugs
Standby power

ABSTRACT

Smart electrical plugs provide appliance-level visibility and control that can support energy conservation in homes, offices, laboratories, and other buildings. Unlike conventional outlets, these devices can measure electrical use, communicate operating data, and disconnect selected loads according to schedules or control rules. This review examines their contribution to four connected objectives: reducing standby consumption, developing appliance consumption profiles, enabling demand-side management, and improving user awareness. The literature is considered through three complementary research areas: smart plug and smart socket implementations, appliance-level and non-intrusive load monitoring, and residential energy management and demand response. The review finds that smart plugs can identify persistent idle loads, reveal differences between active and inactive operating periods, and provide a practical control point for time-based or price-responsive scheduling. However, their effectiveness depends on metering accuracy, appropriate cutoff logic, appliance constraints, communication reliability, and user acceptance. Measurement alone does not guarantee savings, while aggressive disconnection may interrupt essential functions or reduce convenience. The paper therefore proposes an integrated framework linking measurement, profiling, decision-making, and feedback. Research priorities include standardized testing, longer field trials, interoperable platforms, and evaluation of verified net energy savings.

This is an open access article under the CC BY-SA license.

1. INTRODUCTION

Electricity conservation requires more than improving the efficiency of individual appliances because unnecessary operating time and avoidable consumption also contribute to energy waste. Many electronic devices continue drawing electricity when users consider them inactive, particularly when they remain in standby or idle modes. Although the power consumed by one device may be relatively small, the combined effect across numerous appliances and extended periods can become significant. Appliance-level monitoring and control therefore offer a practical opportunity to identify inefficient usage and support more informed electricity management [1]-[3].

Smart electrical plugs, also known as smart sockets or smart outlets, provide an accessible way to monitor and control individual electrical loads. Depending on their design, they can measure voltage, current, power, and accumulated energy while communicating measurements to a local controller or remote application. Their switching functions can disconnect selected appliances according to schedules, user commands, or predefined operating conditions. Previous smart-home research has demonstrated how wireless communication and energy management platforms can coordinate household equipment and support more efficient operation [4]-[6].

Despite these capabilities, several technical and practical questions remain unresolved. Monitoring does not automatically reduce electricity consumption unless users or automated controllers act on the

information, and indiscriminate switching may interfere with appliances that require continuous power. Furthermore, measurement accuracy, standby-state identification, consumer behavior, and the suitability of demand-response strategies influence the actual conservation benefits. This review examines these issues by connecting standby power reduction, consumption profiling, and demand-side management within a unified smart-plug framework.

2. REVIEW SCOPE AND CONCEPTUAL BACKGROUND

The literature is organized into three related groups: smart plug and smart socket implementations, appliance-level monitoring and load disaggregation, and home energy management and demand-response strategies. This approach allows direct smart-plug research to be distinguished from broader studies that provide the analytical methods and control principles needed by smart-plug systems. The resulting synthesis emphasizes technical relevance to energy conservation rather than treating every smart-home technology as a direct smart-plug application.

A smart plug generally combines an electrical interface, measurement circuitry, a switching element, a controller, and a communication interface. The measurement subsystem provides information about connected equipment, while the controller interprets operating conditions and executes switching decisions. Communication technologies allow users or energy management systems to retrieve measurements and issue control commands. The architecture described by Han and Lim [4] and the IoT-enabled smart plug developed by Rokonuzzaman *et al.* [6] illustrate how appliance-level monitoring can be integrated into a wider home energy management environment.

3. STANDBY POWER REDUCTION

Standby consumption is one of the most direct opportunities for smart-plug-based energy conservation. Electronic equipment may continue consuming electricity while waiting for remote commands, maintaining internal memory, powering displays, or keeping communication interfaces active. Conventional switches cannot distinguish between useful standby operation and unnecessary energy consumption, so devices may remain energized for long periods without delivering an immediate service. A smart plug can address this problem by measuring the connected load and disconnecting it when predefined inactivity conditions are satisfied.

Effective standby reduction requires reliable identification of appliance operating states. A low measured power level may indicate standby operation, but it may also represent normal low-power activity, an intermittent operating cycle, or a temporary pause. Consequently, a fixed threshold cannot be applied safely to every appliance category. A more suitable approach combines power thresholds, minimum inactivity duration, operating schedules, and appliance-specific rules to avoid unnecessary disconnection.

The potential for automatic control must also be evaluated against the standby requirements of individual devices. Some equipment can safely be disconnected after use, whereas other appliances require continuous power for clock functions, network availability, data retention, or automatic maintenance. Smart-plug control should therefore distinguish between dispensable standby consumption and functions that users expect to remain available. This distinction is essential for achieving energy savings without creating operational inconvenience.

4. APPLIANCE CONSUMPTION PROFILING AND MONITORING

Consumption profiling converts electrical measurements into information about how and when appliances use energy. Smart plugs can record power and energy measurements at regular intervals, allowing users to examine daily operating patterns, peak consumption periods, and inactive intervals. These records can reveal equipment that remains energized unnecessarily or operates longer than expected. Appliance-level monitoring is particularly useful because aggregate electricity measurements alone may not identify which individual devices contribute most to consumption.

Load identification methods provide an additional analytical capability. Non-intrusive load monitoring (NILM), originally established as a method for estimating individual appliance consumption from aggregate electrical measurements, demonstrates how characteristic power patterns can be used to infer appliance operation [1]. Later research has improved load disaggregation through state-transition constraints, optimization, and machine-learning-based approaches [7]–[9]. Although smart plugs directly measure individual connected loads rather than relying exclusively on aggregate measurements, these techniques remain relevant for classifying operating states and interpreting consumption patterns.

The quality of consumption profiles depends on measurement resolution, sampling frequency, calibration, and data continuity. Low-cost devices may provide useful estimates for routine monitoring, but their readings should not automatically be treated as equivalent to calibrated energy-meter measurements. Short-duration power changes, nonlinear loads, and low-power standby conditions can introduce measurement challenges. Therefore, smart-plug platforms should provide transparent measurement specifications and support comparison against reference instruments.

5. DEMAND-SIDE MANAGEMENT AND INTELLIGENT LOAD CONTROL

Demand-side management (DSM) seeks to influence when and how electricity is consumed in order to improve efficiency, reduce peak demand, or respond to electricity prices and grid requirements. Smart plugs can act as distributed control points because they provide access to individual appliance loads without requiring extensive modification of existing electrical installations. Their measurements can inform scheduling decisions, while switching functions can implement selected control actions. The broader benefits and classifications of demand response have been discussed by Albadi and El-Saadany [10] and Siano [3].

Time-based scheduling is among the simplest DSM strategies for smart plugs. Users can define operating periods for selected appliances, preventing unnecessary operation outside expected usage hours. More advanced systems can use electricity tariffs, predicted consumption, or demand-response signals to shift flexible loads away from expensive or high-demand periods. Research on residential load control and stochastic scheduling demonstrates how these decisions can be optimized while considering electricity prices and household requirements [11]–[13].

Intelligent control can further improve the adaptability of smart-plug systems. Optimization methods and reinforcement learning have been investigated for coordinating household appliances under changing prices, uncertain demand, and user preferences [14]–[17]. These methods can help determine when a controllable appliance should operate, but their practical implementation requires reliable appliance models and clearly defined constraints. Smart plugs are most suitable for loads whose operation can be interrupted or shifted without compromising safety, essential services, or user comfort.

6. INTEGRATED FRAMEWORK AND COMPARATIVE ASSESSMENT

An effective energy-conservation system should connect measurement, operating-state interpretation, control decisions, and user feedback. First, smart plugs collect appliance-level electrical data and transmit it to a local or cloud-based platform. Second, analytical methods identify consumption patterns and distinguish active, idle, and standby conditions. Third, a control strategy determines whether the load should remain connected, be scheduled for later operation, or be disconnected. Finally, historical reports allow users to evaluate energy consumption and assess whether control actions have produced measurable savings.

Table I summarizes the principal research approaches and their contributions to smart-plug-based energy conservation. The comparison distinguishes direct smart-plug implementations from broader monitoring and demand-response research that provides supporting methods. This distinction is important because a successful home energy management algorithm does not necessarily demonstrate the effectiveness of a particular smart-plug product. The table also highlights the need to evaluate monitoring, control, and user requirements together rather than treating them as independent functions.

Table 1. Comparison of research approaches relevant to smart-plug-based energy conservation

Research approach	Representative studies	Main contribution	Relevance to smart plugs
Appliance monitoring and load identification	[1], [7]–[9]	Identification of appliance consumption patterns and operating states	Supports consumption profiling and standby detection
Smart-home communication and monitoring	[4], [6]	Wireless communication, monitoring, and appliance-level control	Provides implementation architectures
Home energy management	[2], [5], [18]	Energy scheduling, system architecture, and intelligent control	Supports integration with household energy systems
Demand response and load scheduling	[10]–[14], [19], [20]	Peak reduction, price-based scheduling, and flexible load management	Enables demand-side control strategies
Learning-based energy management	[15]–[17]	Adaptive scheduling under uncertainty and changing operating conditions	Provides advanced decision-making methods

The comparison indicates that smart plugs can support energy conservation through complementary rather than isolated functions. Monitoring identifies where electricity is being consumed, profiling helps explain when and how consumption occurs, and switching enables corrective action. Demand-response algorithms add a broader system perspective by coordinating flexible loads according to cost, peak demand, or external signals. However, the available literature does not establish that every smart plug provides all these capabilities or delivers equivalent savings under different operating conditions.

7. RESEARCH CHALLENGES AND FUTURE DIRECTIONS

Measurement reliability remains a fundamental challenge because inaccurate readings can lead to incorrect consumption profiles and inappropriate switching decisions. Future smart plugs should be evaluated using standardized procedures that cover resistive, inductive, capacitive, and nonlinear loads, including low-power standby conditions. Researchers should report measurement uncertainty, sampling characteristics, calibration procedures, and switching performance. Such information would improve comparisons between devices and strengthen the credibility of reported energy savings.

Another important challenge concerns the balance between automation and user convenience. A controller that disconnects appliances too frequently may disrupt daily activities or disable functions that users consider essential. Future systems should therefore incorporate appliance-specific operating constraints, user preferences, and manual override facilities. Research should also investigate whether energy feedback and understandable consumption reports encourage sustained behavioral changes rather than temporary reductions.

The integration of smart plugs into larger energy management systems offers further research opportunities. Interoperable communication, secure data exchange, and coordination with smart meters or building management platforms could support more flexible demand-side strategies. Longer field trials are also needed to evaluate seasonal variation, user acceptance, equipment compatibility, and long-term energy savings. Importantly, future studies should report net savings after accounting for the smart plug's own standby consumption and the energy required by its communication and control functions.

8. CONCLUSION

Smart electrical plugs provide a practical means of improving electricity conservation through appliance-level monitoring and controllable power delivery. Their most direct contribution is the identification and reduction of unnecessary standby consumption, while consumption profiling helps users understand appliance operating patterns. When integrated with demand-side management, smart plugs can also support scheduling, load shifting, and peak-demand reduction. Nevertheless, their effectiveness depends on accurate measurement, reliable operating-state identification, appropriate switching logic, and user acceptance. Future development should prioritize standardized performance evaluation, appliance-aware automation, interoperability, and long-term field validation. By combining these elements, smart plugs can evolve from simple remote-controlled outlets into useful components of intelligent and energy-efficient electrical systems.

REFERENCES

[1] G. W. Hart, "Nonintrusive appliance load monitoring," *Proceedings of the IEEE*, vol. 80, no. 12, pp. 1870–1891, 1992, doi: 10.1109/5.192069.

[2] M. Beaudin and H. Zareipour, "Home energy management systems: A review of modelling and complexity," *Renewable and Sustainable Energy Reviews*, vol. 45, pp. 318–335, May 2015, doi: 10.1016/j.rser.2015.01.046.

[3] P. Siano, "Demand response and smart grids—A survey," *Renewable and Sustainable Energy Reviews*, vol. 30, pp. 461–478, Feb. 2014, doi: 10.1016/j.rser.2013.10.022.

[4] D. Han and J. Lim, "Smart home energy management system using IEEE 802.15.4 and zigbee," *IEEE Transactions on Consumer Electronics*, vol. 56, no. 3, pp. 1403–1410, Aug. 2010, doi: 10.1109/tce.2010.5606276.

[5] H. Shareef, M. S. Ahmed, A. Mohamed, and E. Al Hassan, "Review on home energy management system considering demand responses, smart technologies, and intelligent controllers," *IEEE Access*, vol. 6, pp. 24498–24509, 2018, doi: 10.1109/access.2018.2831917.

[6] M. Rokonuzzaman, M. K. Mishu, M. R. Islam, M. I. Hossain, M. Shakeri, and N. Amin, "Design and implementation of an IoT-enabled smart plug socket for home energy management," in *2021 5th International Conference on Smart Grid and Smart Cities (ICSGSC)*, 2021, pp. 50–54, doi: 10.1109/icsgsc52434.2021.9490420.

[7] S. Zeinal-Kheiri, A. M. Shotorbani, and B. Mohammadi-Ivatloo, "Residential load disaggregation considering state transitions," *IEEE Transactions on Industrial Informatics*, vol. 16, no. 2, pp. 743–753, Feb. 2020, doi: 10.1109/tii.2019.2925323.

[8] Y. Guo, X. Xiong, Q. Fu, L. Xu, and S. Jing, "Research on non-intrusive load disaggregation method based on multi-model combination," *Electric Power Systems Research*, vol. 200, p. 107472, Nov. 2021, doi: 10.1016/j.epsr.2021.107472.

[9] İ. H. Çavdar and V. Feryad, "Efficient design of energy disaggregation model with BERT-NILM trained by AdaX optimization method for smart grid," *Energies*, vol. 14, no. 15, p. 4649, 2021, doi: 10.3390/en14154649.

[10] M. H. Albadi and E. F. El-Saadany, "A summary of demand response in electricity markets," *Electric Power Systems Research*, vol. 78, no. 11, pp. 1989–1996, Nov. 2008, doi: 10.1016/j.epsr.2008.04.002.
[11] A.-H. Mohsenian-Rad, V. W. S. Wong, J. Jatskevich, R. Schober, and A. Leon-Garcia, "Autonomous demand-side management based on game-theoretic energy consumption scheduling for the future smart grid," *IEEE Transactions on Smart Grid*, vol. 1, no. 3, pp. 320–331, Dec. 2010, doi: 10.1109/tsg.2010.2089069.
[12] A.-H. Mohsenian-Rad and A. Leon-Garcia, "Optimal residential load control with price prediction in real-time electricity pricing environments," *IEEE Transactions on Smart Grid*, vol. 1, no. 2, pp. 120–133, 2010, doi: 10.1109/tsg.2010.2055903.
[13] Z. Chen, L. Wu, and Y. Fu, "Real-time price-based demand response management for residential appliances via stochastic optimization and robust optimization," *IEEE Transactions on Smart Grid*, vol. 3, no. 4, pp. 1822–1831, Dec. 2012, doi: 10.1109/tsg.2012.2212729.
[14] A. Anvari-Moghaddam, H. Monsef, and A. Rahimi-Kian, "Optimal smart home energy management considering energy saving and a comfortable lifestyle," *IEEE Transactions on Smart Grid*, vol. 6, no. 1, pp. 324–332, Jan. 2015, doi: 10.1109/tsg.2014.2349352.
[15] R. Lu, S. H. Hong, and M. Yu, "Demand response for home energy management using reinforcement learning and artificial neural network," *IEEE Transactions on Smart Grid*, vol. 10, no. 6, pp. 6629–6639, Nov. 2019, doi: 10.1109/tsg.2019.2909266.
[16] L. Yu *et al.*, "Deep reinforcement learning for smart home energy management," *IEEE Internet of Things Journal*, vol. 7, no. 4, pp. 2751–2762, Apr. 2020, doi: 10.1109/jiot.2019.2957289.
[17] H. Li, Z. Wan, and H. He, "Real-time residential demand response," *IEEE Transactions on Smart Grid*, vol. 11, no. 5, pp. 4144–4154, 2020, doi: 10.1109/tsg.2020.2978061.
[18] K. Salameh, M. Awad, A. Makarfi, A.-H. Jallad, and R. Chbeir, "Demand side management for smart houses: a survey," *Sustainability*, vol. 13, no. 12, p. 6768, 2021, doi: 10.3390/su13126768.
[19] H. Apaydin-Özkan, "An appliance scheduling system for residential energy management," *Sensors*, vol. 21, no. 9, p. 3287, May 2021, doi: 10.3390/s21093287.
[20] S. H. Hong, M. Yu, and X. Huang, "A real-time demand response algorithm for heterogeneous devices in buildings and homes," *Energy*, vol. 80, pp. 123–132, Feb. 2015, doi: 10.1016/j.energy.2014.11.053.